**14" Decorative Round Opal Diffusers**


<b>H2552</b>	(2) 60W A19
<b>H2552FL28</b>	28W 2D Fluorescent Lamp (120V input)
<b>H2552EFL28U</b>	28W 2D Fluorescent Lamp with Electronic Ballast (120/277V universal input)
<b>H2553</b>	(1) 22W and (1) 32W Circline Fluorescent (120V input)

**Notes:** Frosted Polycarbonate Diffuser with Black Base. UL Damp Location Listed. Includes tamper resistant screws (SD2925 Screwdriver required)

**10" Decorative Round Opal Diffusers**


<b>H2550</b>	(2) 60W A19
<b>H2550FL16</b>	16W 2D Fluorescent Lamp (120V input)
<b>H2550EFL16</b>	16W 2D Fluorescent Lamp with Electronic Ballast (120V input)
<b>H2551</b>	22W Circline0 Fluorescent (120V input)

**Notes:** Frosted polycarbonate Diffuser with Black Base. UL Damp Location Listed. Includes tamper resistant screws (SD2925 Screwdriver required)

**Wall or Ceiling Mount Opal Rectangle Diffusers**

<b>H2561</b>	60W A19
<b>H2562</b>	13W Compact Fluorescent Lamp (120V input)

**Notes:** Frosted Diffuser with Die Cast Black Base. UL Wet Location Listed. Includes tamper resistant screws (SD2925 Screwdriver required)

**H2513 Ultra Shallow Surface**

**Lamp:** (2) 13W TT Twin Tube Compact Fluorescent

Linear spread lens provides radical batwing distribution ideal for lighting walls in corridors. Black reveal at ceiling provides soft uplight to reduce ceiling contrast. Spun aluminum housing with NPF ballasts

**Finish:** White (W)

